

EC16002



**DOUBLE SIDED MODULAR BOXES 2+2
DEVICES WITH 60 mm CENTRE HOLE -
SLATE GREY**



Trunkings > Floor cable management > Floor distribution systems > Utility floor boxes > Modular floor box for wiring devices > Floor boxes

Technical Symbols/Marks/Approvals

IK07	IP54	GWT 650°	CE	RoHS II	MADE IN ITALY
------	------	-------------	----	---------	---------------------

Norms

EN 50085-1 EN 50085-2-4

Description

Double-sided tower made of shock-resistant technopolymer. Designed for 4+4 fixtures with 108.5 mm spacing or for 2+2 fixtures with 60 mm spacing. End cap included for single-sided use. Designed for the entry of 75x17 and 50x12 mm floor trunking. Can be installed on poured or raised floors.

Etim

GROUP EG000005 - Subfloor electrical installation systems

CLASS EC000121 - Surface tank empty


Material	Other	Surface protection	Other	Colour	Anthracite
Width	150 mm	Height	149 mm	Model	Horizontal
Length	226 mm	RAL-number	7021	Number of appliances to build in	8
Number of units to build in front side	4	Number of units to build in rear side	4	Suitable for standard switching equipment	Yes
Suitable for wet cleaning	Yes				

Technical Characteristics

IP Grade	54	wheelbase	108 mm
-----------------	----	------------------	--------

Documentation available for download

Instruction booklet



Istruzioni_SERIE_1
60_0423.pdf

Barcode



8033576771779

Unit

1 NR

0.2x0.154x0.145 [m]

0.791 [kg]



8059307212472

Cardboard

10 NR

0.605x0.4x0.35 [m]

7.91 [kg]