

ECICTA50GC

HF ICTA PLIABLE PP CONDUIT 34223 Ø50 mm - 25 m - LIGHT GREY - RAL 7035



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Conduits and fittings > Conduits > Corrugated conduits >
Series icta - pp - class 34223 - 750 n > plastic conduits > Black

Technical Symbols/Marks/Approvals

HF

GWT
850°

+90°



RoHS II

MADE
IN
ITALY

Norms

EN 61386-1 EN 61386-22 EN 61034-2 EN 50642

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polypropylene (PP)	Halogen free	Yes
Colour	Grey	RAL-number	7035	UV resistant	No
Suitable for underground installation	No	Operating temperature	-5-90 °C	Bending strength	Pliable, self recovering
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Heavy (class 4 / 6 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	No	Suitable for installation on wood	Yes
Suitable for hollow wall installation	Yes	Suitable for concrete installation	Yes	Machine and systems installation	No
Suitable for underfloor installation (screed)	Yes	Suitable for outdoor installation	No	Outer diameter	50 mm
High conducting inner coating	Yes	With metre indication	No		

Documentation available for download

Certification

Test Report ICTA
Contenuto alogeni
MI23-0092109-
01.pdf

Brochure

BROCHURE TUBI
doppie.pdf

Barcode



8056351668330

Cardboard

25 MT

4.87 [kg]



8056351668392

Pallet

800 MT

155.84 [kg]