

ECTC1840T



**PLIABLE PVC CONDUIT 33412 Ø40 mm
- 25 m WITH DRAW TAPE**

Conduits and fittings > Conduits > Corrugated conduits >
Series tc18 - pvc -25°C - class 33412 - 750 n > plastic conduits
> Grey - cable puller



IMMAGINE RAPPRESENTATIVA **EC** REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-22

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7031	UV resistant	No
Suitable for underground installation	No	Operating temperature	-25-60 °C	Bending strength	Pliable
With sleeve	No	Fire retardant version	Yes	Surface mounting	No
Suitable for installation on wood	No	Suitable for hollow wall installation	No	Suitable for concrete installation	Yes
Machine and systems installation	No	Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No
Inner diameter	31.2 mm	Outer diameter	40 mm	High conducting inner coating	No
With metre indication	No				

Documentation available for download

Certification

OVE_50017-002-09.pdf

Certification

OVE_50017-002-10.pdf

Barcode



8054320282778

Cardboard

25 MT

5.225 [kg]



8054320283119

Pallet

1000 MT

209 [kg]