



DRY LINING INSTALLATION BOX 3 MODULE - HOLE CENTRE DISTANCE 83,5





Enclosures > Recessed > Boxes for wiring devices > Series 340 - dry lining > Flush mount junction boxes > Rectangular boxes

Technical Symbols/Marks/Approvals

IP40 GWT CE ROHS II MADE IN ITALY

Norms

EN 60670-1 CEI 23-74

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002601 - Box/housing for built-in mounting in the wall/ceiling

Mounting method	Hollow wall	Degree of protection (IP)	IP00	Material	Plastic
Halogen free	No	Surface protection	Untreated	Colour	Blue
Width	113 mm	Model	Other	Length	72 mm
Cover model	None	Inner depth	50 mm	Circuit integrity	None
Equipped with	None	Shape	Rectangular	Number of inlets	12
Inlet from the rear	Yes	Compliant with BS 4662	No	Couplable	No
Transparent cover	No	Pipe locking	No	Construction Built-in installation type	n box (device box)
Airtight	No	For tube diameter	20/25 mm	Cover attachment	Screwed
Sealable	No	With screening	No	Provided with revolving ring	No
Depth	0-50 mm	For number of device inserts	3	Mounting switching equipment	Screwing
With screws	No	Housing feed-through by break- out opening	Yes	Housing feed-through by seal membrane	No
Housing feed-through by nozzle	No	Housing feed-through by step membrane	No	Pipe locking optional	No
Number of included spouts	0	Clamp position fixed	No	Luminaire hook mounting	No
Nozzle	None	Special application	None	With partition panel	No





Barcode




8054320284017

Pack

10 NR

0.255x0.07x0.23 [m]

0.6 [kg]



8057711599455

Cardboard

300 NR

0.605x0.405x0.55 [m]

18 [kg]