

EC34006

DRY LINING INSTALLATION BOX 6 MODULES - HOLE CENTRE DISTANCE 100

Enclosures > Recessed > Boxes for wiring devices > Series 340 - dry lining > Flush mount junction boxes > Rectangular boxes

Technical Symbols/Marks/Approvals

GWT 850° | CE | RoHS II | MADE IN ITALY

Norms

EN 60670-1 CEI 23-74

Description

Flush-mounting box for hollow walls (plasterboard or wood). Made of shock-resistant, low-smoke blue technopolymer. Resistance to abnormal heat up to 850°C (Glow Wire Test - GWT). 68 mm diameter drilling centers integrated into the bottom of the box. Fixed to the structure using adjustable clips. Manufactured in compliance with EN 60670-1:2021 +A11:2021 standards. Installation temperatures: minimum –5°C, maximum +60°C.
Dimensions: 188x70x50 mm
6/7 modules, 100 mm center-to-center distance

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002601 - Box/housing for built-in mounting in the wall/ceiling

Mounting method	Hollow wall	**Degree of protection (IP)**	IP00	**Material**	Plastic
Halogen free	No	**Surface protection**	Untreated	**Colour**	Blue
Width	188 mm	**Model**	Other	**Length**	72 mm
Cover model	None	**Inner depth**	50 mm	**Circuit integrity**	None
Equipped with	None	**Shape**	Rectangular	**Number of inlets**	16
Inlet from the rear	Yes	**Compliant with BS 4662**	No	**Couplable**	No
Transparent cover	No	**Pipe locking**	No	**Construction type**	Built-in installation box (device box)
Airtight	No	**For tube diameter**	20/25 mm	**Cover attachment**	Screwed
Sealable	No	**With screening**	No	**Provided with revolving ring**	No
Depth	0-50 mm	**For number of device inserts**	6	**Mounting switching equipment**	Screwing
With screws	No	**Number of adjustable device fixing lugs**	2	**Housing feed-through by break-out opening**	Yes
Housing feed-through by seal membrane	No	**Housing feed-through by nozzle**	No	**Housing feed-through by step membrane**	No
Pipe locking optional	No	**Number of included spouts**	0	**Clamp position fixed**	No
Luminaire hook mounting	No	**Nozzle**	None	**Special application**	None
With partition panel	No				

Dimensions and technical drawings

EC34006_2026.pdf

Barcode

8054320283997
Pack
10 NR
0.255x0.065x0.38 [m]
0.688 [kg]

8057711599479
Cardboard
160 NR
0.405x0.605x0.55 [m]
11.008 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.