

EC34045



DRY LINING JUNCTION BOX 80X45

Enclosures > Recessed > Boxes for wiring devices > Series 340 - dry lining > Flush mount junction boxes > Round boxes



Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-22

Description

Flush-mounting junction box for hollow walls (plasterboard or wood). Made of shock-resistant, low-smoke blue technopolymer. Complete with cover and fixing screws. Resistance to abnormal heat up to 850°C (Glow Wire Test - GWT). 68 mm diameter drilling centers integrated into the bottom of the box. Fixed to the structure using adjustable clips. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2006 standards. Installation temperatures: minimum -5°C, maximum +60°C. Protection degree IP40. Dimensions: diameter 83x45 mm

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002601 - Box/housing for built-in mounting in the wall/ceiling

Mounting method	Hollow wall	Degree of protection (IP)	IP00	Material	Plastic
Halogen free	No	Surface protection	Untreated	Colour	Blue
Width	80 mm	Model	Other	Diameter	86 mm
Cover model	None	Inner depth	46 mm	Circuit integrity	None
Equipped with	None	Shape	Round	Number of inlets	8
Inlet from the rear	Yes	Compliant with BS 4662	No	Couplable	No
Transparent cover	No	Pipe locking	No	Construction type	Cable junction box
Airtight	No	For tube diameter	20/25 mm	Cover attachment	Screwed
Sealable	No	With screening	No	Provided with revolving ring	No
Depth	0-46 mm	For number of device inserts	1	With screws	No
Housing feed-through by break-out opening	Yes	Housing feed-through by seal membrane	No	Housing feed-through by nozzle	No
Housing feed-through by step membrane	No	Pipe locking optional	No	Number of included spouts	0
Clamp position fixed	No	Luminaire hook mounting	No	Nozzle	None
Special application	None	With partition panel	No		

Barcode



8054320283959

Pack

10 NR

0.08x0.08x0.465 [m]

0.294 [kg]



8057711599516

Cardboard

350 NR

0.405x0.61x0.515 [m]

10.29 [kg]