

EC350C1



FLUSH MOUNTING JUNCTION BOX WITH LID DIM. 92X92X45

Enclosures > Recessed > Recessed junction boxes > Series 350 - masonry > Flush mount junction boxes > Orange boxes



Technical Symbols/Marks/Approvals

IP40	HF	GWT 650°	CE	RoHS II		MADE IN ITALY
------	----	----------	----	---------	--	---------------

Norms

EN 60670-1 EN 60670-22

Description

Recessed junction box for masonry walls. Made of impact-resistant, halogen-free technopolymer. Complete with cover and fixing screws. Paintable embossed cover. Resistance to abnormal heat up to 650°C (GWT). Manufactured in accordance with EN 60670-1:2005, EN 60670-22:2006. Installation temperatures: minimum -15°C, maximum +60°C. IP40 protection rating. Dimensions: 92x92x45 mm

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002601 - Box/housing for built-in mounting in the wall/ceiling

Max. conductor cross section	0	Mounting method	Flush-mounted	Degree of protection (IP)	IP40
Material	Plastic	Halogen free	Yes	Surface protection	Untreated
Colour	Orange	Width	91 mm	Model	Other
Length	91 mm	Diameter	0 mm	Cover model	Blind cover
Inner depth	44 mm	Circuit integrity	None	Equipped with	None
Shape	Square	Number of inlets	11	Inlet from the rear	Yes
Compliant with BS 4662	No	Couplable	No	Transparent cover	No
Pipe locking	No	Construction type	Cable junction box	Airtight	No
For tube diameter	Other	Cover attachment	Screwed	Sealable	No
With screening	No	Provided with revolving ring	No	Depth	0-44 mm
For number of device inserts	0	Mounting switching equipment	Screwing	With screws	Yes
Housing feed-through by break-out opening	Yes	Housing feed-through by seal membrane	No	Housing feed-through by nozzle	No
Housing feed-through by step membrane	No	Pipe locking optional	No	Number of included spouts	0
Number of poles of the clamp	0	Clamp position fixed	No	Luminaire hook mounting	No
Nozzle	None	Special application	None	With partition panel	No

Technical Characteristics


Preparation for
compartments/DIN rails

Documentation available for download




Certification
Serie 350
IMQ_CA02.01670_
2018.pdf

Barcode



8032636760609
Unit
1 NR
0.115x0.05x0.115 [m]
0.0729 [kg]



8057711599523
Cardboard
240 NR
0.405x0.605x0.55 [m]
17.496 [kg]