

**EC350C3**

**FLUSH MOUNTING JUNCTION BOX  
WITH LID DIM. 120X100X70**



Enclosures > Recessed > Recessed junction boxes > Series 350 - masonry > Flush mount junction boxes > Orange boxes



**Technical Symbols/Marks/Approvals**



**Norms**

EN 60670-1 EN 60670-22

**Description**

Recessed junction box for masonry walls. Made of impact-resistant, halogen-free technopolymer. Complete with cover and fixing screws. Paintable embossed cover. Resistance to abnormal heat up to 650°C (GWT). Manufactured in accordance with EN 60670-1:2005, EN 60670-22:2006. Installation temperatures: minimum -15°C, maximum +60°C. IP40 protection rating. Dimensions: 120x100x70 mm

**Etim**

**GROUP EG000048 - Connection material (electrotechnical)**

**CLASS EC002601 - Box/housing for built-in mounting in the wall/ceiling**

<b>Max. conductor cross section</b>	0	<b>Mounting method</b>	Flush-mounted	<b>Degree of protection (IP)</b>	IP40
<b>Material</b>	Plastic	<b>Halogen free</b>	Yes	<b>Surface protection</b>	Untreated
<b>Colour</b>	Orange	<b>Width</b>	119 mm	<b>Model</b>	Other
<b>Length</b>	96 mm	<b>Diameter</b>	0 mm	<b>Cover model</b>	Blind cover
<b>Inner depth</b>	69 mm	<b>Circuit integrity</b>	None	<b>Equipped with</b>	None
<b>Shape</b>	Rectangular	<b>Number of inlets</b>	11	<b>Inlet from the rear</b>	Yes
<b>Compliant with BS 4662</b>	No	<b>Couplable</b>	No	<b>Transparent cover</b>	No
<b>Pipe locking</b>	No	<b>Construction type</b>	Cable junction box	<b>Airtight</b>	No
<b>For tube diameter</b>	Other	<b>Cover attachment</b>	Screwed	<b>Sealable</b>	No
<b>With screening</b>	No	<b>Provided with revolving ring</b>	No	<b>Depth</b>	0-69 mm
<b>For number of device inserts</b>	0	<b>Mounting switching equipment</b>	Screwing	<b>With screws</b>	Yes
<b>Housing feed-through by break-out opening</b>	Yes	<b>Housing feed-through by seal membrane</b>	No	<b>Housing feed-through by nozzle</b>	No
<b>Housing feed-through by step membrane</b>	No	<b>Pipe locking optional</b>	No	<b>Number of included spouts</b>	0
<b>Number of poles of the clamp</b>	0	<b>Clamp position fixed</b>	No	<b>Luminaire hook mounting</b>	No
<b>Nozzle</b>	None	<b>Special application</b>	None	<b>With partition panel</b>	No

## Technical Characteristics


Preparation for  
compartments/DIN rails

## Documentation available for download



**Certification**  
Serie 350  
IMQ\_CA02.01670\_  
2018.pdf

## Barcode



8032636760623  
**Unit**  
1 NR  
0.125x0.075x0.14 [m]  
0.1 [kg]



8057711599547  
**Cardboard**  
100 NR  
0.405x0.605x0.55 [m]  
10 [kg]