

**EC37065**

**FLUSH MOUNTING ROUND BOX DIM.  
60X40**



Enclosures > Recessed > Boxes for wiring devices > Series 37  
- masonry recessed boxes > Flush mount junction boxes for  
wiring devices > Round boxes - orange

**Technical Symbols/Marks/Approvals**



**Norms**

EN 60670-1 EN 60670-22

**Description**

Flush-mounting junction or device box for masonry walls. Made of shock-resistant, halogen-free technopolymer in orange. Resistance to abnormal heat: 650°C (Glow Wire Test - GWT). For the installation of domestic wiring devices. Lateral knockouts for easy installation and conduit entry. Manufactured in compliance with EN 60670-1:2021 +A11:2021 standards. Installation temperatures: minimum -15°C, maximum +60°C.  
Diameter 60x40 mm

## Etim

### GROUP EG000048 - Connection material (electrotechnical)

### CLASS EC002601 - Box/housing for built-in mounting in the wall/ceiling

|  |  |                                       |               |  |           |
|--|--|---------------------------------------|---------------|--|-----------|
| <b>Max. conductor cross section</b>          | 0                                      | <b>Mounting method</b>                | Flush-mounted | <b>Degree of protection (IP)</b>                 | IP00      |
| <b>Material</b>                              | Plastic                                | <b>Halogen free</b>                   | Yes           | <b>Surface protection</b>                        | Untreated |
| <b>Colour</b>                                | Orange                                 | <b>Width</b>                          | 0 mm          | <b>Model</b>                                     | Other     |
| <b>Diameter</b>                              | 60 mm                                  | <b>Cover model</b>                    | None          | <b>Inner depth</b>                               | 40 mm     |
| <b>Circuit integrity</b>                     | None                                   | <b>Equipped with</b>                  | None          | <b>Shape</b>                                     | Round     |
| <b>Number of inlets</b>                      | 3                                      | <b>Inlet from the rear</b>            | Yes           | <b>Compliant with BS 4662</b>                    | No        |
| <b>Couplable</b>                             | No                                     | <b>Transparent cover</b>              | No            | <b>Pipe locking</b>                              | No        |
| <b>Construction type</b>                     | Built-in installation box (device box) | <b>Airtight</b>                       | No            | <b>For tube diameter</b>                         | 20/25 mm  |
| <b>Cover attachment</b>                      | Other                                  | <b>Sealable</b>                       | No            | <b>With screening</b>                            | No        |
| <b>Provided with revolving ring</b>          | No                                     | <b>Depth</b>                          | 0-40 mm       | <b>For number of device inserts</b>              | 2         |
| <b>Mounting switching equipment</b>          | Screwing                               | <b>With screws</b>                    | No            | <b>Housing feed-through by break-out opening</b> | Yes       |
| <b>Housing feed-through by seal membrane</b> | No                                     | <b>Housing feed-through by nozzle</b> | No            | <b>Housing feed-through by step membrane</b>     | No        |
| <b>Pipe locking optional</b>                 | No                                     | <b>Number of included spouts</b>      | 0             | <b>Number of poles of the clamp</b>              | 0         |
| <b>Clamp position fixed</b>                  | No                                     | <b>Luminaire hook mounting</b>        | No            | <b>Nozzle</b>                                    | None      |
| <b>Special application</b>                   | None                                   | <b>With partition panel</b>           | No            |  |           |

## Barcode



8054320283850

**Pack**

10 NR

0.06x0.06x0.42 [m]

0.158 [kg]



8057711599615

**Cardboard**

600 NR

0.39x0.565x0.61 [m]

9.48 [kg]