

EC63212FPL

FLUSH-MOUNT BOX FOR 12M (1x12) ENCLOSURE - HOLLOW-WALLS



Enclosures > Recessed > Recessed modular enclosures > Series 632 essenza - modular enclosures > Small distribution board > Recessed dry-lining box

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Description

Flush-mounting back box for lightweight walls - plasterboard or wood. Made of high-impact technopolymer with low smoke emission. Resistance to abnormal heat up to 850°C (GWT). Base fixing to the structure via brackets. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperature range: minimum -15°C, maximum +60°C. Dimensions 296x219 mm. Depth 80 mm. 12 DIN modules.

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board


Mounting method	Hollow wall	Width in number of modular spacings	12	Built-in depth	80 mm
Colour	Blue	Width	296 mm	Height	219 mm
Depth	80 mm	Built-in height	80 mm	UV resistant	No
Transparent cover/door	No	With lock	No	Inner depth	76 mm
Number of rows	1	Extension possible	No	Housing material	Plastic
With mounting plate	No	Type of closure	Other	DIN-rail	No
EMC-version	No				

Technical Characteristics

dimensions 296x219x80 mm

Documentation available for download

Instruction booklet



Istruzioni 630-
635_0125_0125.pdf

Dimensions and technical drawings



EC63212_FONDO_
PL_2025.pdf

Barcode



8055035962894

Unit

1 NR

0.25x0.33x0.11 [m]

0.4284 [kg]



8055035963006

Cardboard

5 NR

0.6x0.41x0.28 [m]

2.142 [kg]