

EC63224CE

ESSENZA MOD. ENCLOSURE - 24 WAYS - WHITE - TERM. BLOCK

Enclosures > Recessed > Recessed modular enclosures > Series 632 essenza - modular enclosures > Small distribution board > Enclosure frame - white - equipped



Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Description

Flush-mounting distribution board front for masonry or plasterboard walls. Resistance to abnormal heat up to 650°C (GWT). Cover and door made of halogen-free ABS technopolymer. Reversible cover. Self-adhesive circuit identification labels included. Blanking covers for unused modules included. Galvanized steel DIN rail mounted on a removable support for perfect horizontal alignment. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperature range: minimum -15°C, maximum +60°C. IP40 protection degree.

External dimensions 328x390x11 mm

24 DIN modules

4 terminal blocks 6x10 mm - 12 holes

Dissipated power 35 W

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board


Mounting method	Flush-mounted/hollow wall	Degree of protection (IP)	IP40	Width in number of modular spacings	24
Built-in depth	80 mm	Colour	White	Width	328 mm
Height	390 mm	Depth	91 mm	Built-in height	80 mm
RAL-number	9001	UV resistant	No	Type of covering	Door
Cover model	Closed	Type of door	Single	Transparent cover/door	No
With lock	No	Inner depth	76 mm	Number of rows	2
Extension possible	No	Housing material	Plastic	With mounting plate	No
Type of closure	Other	Earthing terminal block	Yes	Neutral terminal block	Yes
DIN-rail	Yes	EMC-version	No		

Technical Characteristics

dimensions	328x390x11 mm	Terminal blocks/holes	4x12	Power dissipation	35 W
Tipo_Morsettiera	2x16 + 10x10 mm ²				


Documentation available for download

Instruction booklet



Istruzioni 630-
635_0125_0125.pdf

Dimensions and technical drawings

 EC63224_2025.pdf

Barcode



8055035962931

Unit

1 NR

0.41x0.33x0.18 [m]

1.595 [kg]