

EC63224F

FLUSH-MOUNT BOX FOR 24M (2x12) ENCLOSURE - BRICK-WALLS

Enclosures > Recessed > Recessed modular enclosures > Series 632 essenza - modular enclosures > Small distribution board > Recessed masonry box

Technical Symbols/Marks/Approvals

IP40 | GWT 650° | RoHS II | MADE IN ITALY

Norms

EN 60670-1 EN 60670-24

Description

Flush-mounting back box for masonry walls. Made of high-impact technopolymer with low smoke emission. Resistance to abnormal heat up to 650°C (GWT). Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperature range: minimum -15°C, maximum +60°C.
Dimensions 296x368 mm
Depth 80 mm
24 DIN modules

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board


Mounting method	Flush-mounted	**Width in number of modular spacings**	24	**Built-in depth**	80 mm
Colour	Orange	**Width**	296 mm	**Height**	368 mm
Depth	80 mm	**Built-in width**	297 mm	**Built-in height**	80 mm
RAL-number	2004	**UV resistant**	No	**Transparent cover/door**	No
With lock	No	**Inner depth**	76 mm	**Number of rows**	2
Extension possible	No	**Housing material**	Plastic	**With mounting plate**	No
Signal passing door	No	**Type of closure**	Other	**Earthing terminal block**	No
Neutral terminal block	No	**DIN-rail**	No	**EMC-version**	No

Technical Characteristics

dimensions	368x296x80 mm

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Instruction booklet

Istruzioni 630-635_0125_0125.pdf

Dimensions and technical drawings

EC63224_FONDO_2025.pdf

Barcode

8055035962948

Unit

1 NR

0.25x0.33x0.105 [m]

0.71 [kg]

8055035963013

Cardboard

4 NR

0.6x0.41x0.28 [m]

2.84 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.