

EC63224FPL

FLUSH-MOUNT BOX FOR 24 WAYS ENCLOSURE - HOLLOW-WALLS

Enclosures > Recessed > Recessed modular enclosures > Series 632 essenza - modular enclosures > Small distribution board > Recessed dry-lining box



Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Description

Flush-mounting back box for lightweight walls - plasterboard or wood. Made of high-impact technopolymer with low smoke emission. Resistance to abnormal heat up to 850°C (GWT). Base fixing to the structure via brackets. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperature range: minimum -15°C, maximum +60°C.

Dimensions 296x368 mm

Depth 80 mm

24 DIN modules

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board


Mounting method	Hollow wall	Width in number of modular spacings	24	Built-in depth	80 mm
Colour	Blue	Width	296 mm	Height	368 mm
Depth	80 mm	Built-in height	80 mm	UV resistant	No
Transparent cover/door	No	With lock	No	Inner depth	76 mm
Number of rows	2	Extension possible	No	Housing material	Plastic
With mounting plate	No	Type of closure	Other	DIN-rail	No
EMC-version	No				

Technical Characteristics

dimensions 368x296x80 mm

Documentation available for download

Instruction booklet



Istruzioni 630-
635_0125_0125.pdf

Dimensions and technical drawings

EC63224_FONDO_PL_2025.pdf

Barcode



8055035962955

Unit

1 NR

0.25x0.33x0.105 [m]

0.73 [kg]



8055035963020

Cardboard

4 NR

0.6x0.41x0.28 [m]

2.92 [kg]