


## EC63224N

### ESSENZA MOD. ENCLOSURE - 24 WAYS - BLACK

Enclosures > Recessed > Recessed modular enclosures > Series 632 essenza - modular enclosures > Small distribution board > Enclosure frame - black



#### Technical Symbols/Marks/Approvals



#### Norms

EN 60670-1 EN 60670-24

## Description

Flush-mounting distribution board front for masonry or plasterboard walls. Resistance to abnormal heat up to 650°C (GWT). Cover and door made of halogen-free ABS technopolymer. Reversible cover. Self-adhesive circuit identification labels included. Blanking covers for unused modules included. Galvanized steel DIN rail mounted on a removable support for perfect horizontal alignment. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperature range: minimum -15°C, maximum +60°C. IP40 protection degree.

External dimensions 328x390x11 mm

24 DIN modules

Dissipated power 35 W

## Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board

<b>Mounting method</b>	Flush-mounted/hollow wall	<b>Degree of protection (IP)</b>	IP40	<b>Width in number of modular spacings</b>	24
<b>Built-in depth</b>	80 mm	<b>Colour</b>	Black	<b>Width</b>	328 mm
<b>Height</b>	390 mm	<b>Depth</b>	91 mm	<b>Built-in height</b>	80 mm
<b>RAL-number</b>	7021	<b>UV resistant</b>	No	<b>Type of covering</b>	Door
<b>Cover model</b>	Closed	<b>Type of door</b>	Single	<b>Transparent cover/door</b>	Yes
<b>With lock</b>	No	<b>Inner depth</b>	76 mm	<b>Number of rows</b>	2
<b>Extension possible</b>	No	<b>Housing material</b>	Plastic	<b>With mounting plate</b>	No
<b>Type of closure</b>	Other	<b>DIN-rail</b>	Yes	<b>EMC-version</b>	No

## Technical Characteristics

<b>dimensions</b>	328x390x11 mm	<b>Power dissipation</b>	35 W
-------------------	---------------	--------------------------	------

## Documentation available for download

### Instruction booklet



Istruzioni 630-  
635\_0125\_0125.pdf

## Dimensions and technical drawings



EC63224\_2025.pdf

## Barcode



8055035962962

### Unit

1 NR

0.25x0.33x0.105 [m]

1.497 [kg]