

ECRCA25

TEAR-PROOF FITTINGS FOR CORRUGATED CONDUIT D.25 mm

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Joint for corrugeted conduits > Openable joints for corrugated conduits

Technical Symbols/Marks/Approvals

IP40 | HF | GWT 650° | CE | RoHS II | MADE IN ITALY | UV

Norms

EN 61386-1 EN 61386-22

Description

Strain-relief fitting for Halogen-Free polypropylene corrugated pipe. UV resistant. Resistance to abnormal heat (GWT, IEC 60695-2-11 standard): up to 650°C. Protection rating: IP40. Insulation resistance > 100 MΩ. Installation temperature: minimum -5°C, maximum +90°C.
Regulatory references: EN 61386-1, EN 61386-22.
Nominal internal diameter 25 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001492 - Coupler for cable protection tube for underground application

Material	Plastic	**Material quality**	Polypropylene (PP)	**Halogen free**	Yes
Surface protection	Untreated	**Colour**	Black	**UV resistant**	Yes
Surface polished	No	**Separable**	Yes	**Inner diameter**	25 mm
Outer diameter	28.4 mm	**Nominal diameter, connection 1**	25 mm	**Nominal diameter, connection 2**	25 mm
Reducing	No	**With rubber seal**	No		

Technical Characteristics

length	65 mm

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

Test Report Serie ICTA-RCA-UV MI-0137744-01.pdf

Barcode

8055035963068

Pack

100 NR

1.1 [kg]

8055035963075

Cardboard

700 NR

0.605x0.4x0.26 [m]

7.7 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.