elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECRCA32

TEAR-PROOF FITTINGS FOR CORRUGATED CONDUIT D.32 mm

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Joint for corrugeted conduits > Openable joints for corrugated conduits

Technical Symbols/Marks/Approvals

IP40 | HF | GWT 650° | CE | RoHS II | MADE IN ITALY | UV

Norms

EN 61386-1 EN 61386-22

Description

Strain-relief fitting for Halogen-Free polypropylene corrugated pipe. UV resistant. Resistance to abnormal heat (GWT, IEC 60695-2-11 standard): up to 650°C. Protection rating: IP40. Insulation resistance > 100 MΩ. Installation temperature: minimum -5°C, maximum +90°C.
Regulatory references: EN 61386-1, EN 61386-22.
Nominal internal diameter 32 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001492 - Coupler for cable protection tube for underground application

Material	Plastic	**Material quality**	Polypropylene (PP)	**Halogen free**	Yes
Surface protection	Untreated	**Colour**	Black	**UV resistant**	Yes
Surface polished	No	**Separable**	Yes	**Inner diameter**	32 mm
Outer diameter	35.4 mm	**Nominal diameter, connection 1**	32 mm	**Nominal diameter, connection 2**	32 mm
Reducing	No	**With rubber seal**	No		

Technical Characteristics

length	65 mm

Documentation available for download



Certification

Test Report Serie ICTA-RCA-UV MI-0137744-01.pdf

Barcode

8055035963099
Pack
50 NR
0.71 [kg]

8055035963105
Cardboard
400 NR
0.605x0.4x0.26 [m]
5.68 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.