

ECICTA40BL

HF ICTA PLIABLE PP CONDUIT 34223 Ø40 mm - 25 m - BLUE



IMMAGINE
RAPPRESENTATIVA

Conduits and fittings > Conduits > Corrugated conduits >
Series icta - pp - class 34223 - 750 n > plastic conduits > Black

Technical Symbols/Marks/Approvals

HF	GWT 850°	+90°		CE	RoHS II	MADE IN ITALY
----	-------------	------	--	----	---------	---------------------

Norms

EN 61386-1 EN 61386-22 EN 61034-2 EN 50642

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polypropylene (PP)	Halogen free	Yes
Colour	Blue	RAL-number	5005	UV resistant	No
Suitable for underground installation	No	Operating temperature	-5-90 °C	Bending strength	Pliable, self recovering
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Heavy (class 4 / 6 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	No	Suitable for installation on wood	Yes
Suitable for hollow wall installation	Yes	Suitable for concrete installation	Yes	Machine and systems installation	No
Suitable for underfloor installation (screed)	Yes	Suitable for outdoor installation	No	Inner diameter	30.7 mm
Outer diameter	40 mm	High conducting inner coating	Yes	With metre indication	No

Documentation available for download

Certification

Test Report ICTA
Contenuto alogeni
MI23-0092109-01.pdf

Brochure

BROCHURE TUBI
doppie.pdf

Barcode



8055035963259

Cardboard

25 MT

3.975 [kg]



8055035963266

Pallet

1000 MT

159 [kg]