

EC400C6

JUNCTION BOX IP55 WITH STEPPED GLANDS DIM. 190X140X70



Enclosures > Wall-mount > Wall-mount junction boxes > Series 400 - nipple version > Wall mount junction boxes > Ip65

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-22

Description

Junction box with soft material concentric cable glands. Manufactured in shockproof, UV-resistant, and halogen-free technopolymer (ABS-based). Impact resistance rating IK08. Glow Wire Test (GWT) resistance up to 650°C. Lid secured with stainless steel screws. Screw tightening torque 0.8 Nm. High-adhesion soft rubber internal gasket. Double insulation capability via optional plugs. Internal fixing points for DIN rails, terminal blocks, or backplates. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2006 standards. Installation temperature range: minimum -5°C, maximum +60°C. Operating temperature range: minimum -25°C, maximum +70°C. Protection degree IP55.

Dimensions: 150x140x70 mm

10 inlets for 32 mm diameter conduits

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Rated insulation voltage Ui	400 V	Mounting method	Wall-/ceiling mounting	Degree of protection (IP)	IP55
Material	Plastic	Halogen free	No	Surface protection	Untreated
Colour	Grey	Width	190 mm	Depth	70 mm
Model	Junction box	Length	140 mm	Diameter	0 mm
Working temperature	-25-70 °	Explosion-tested version	No	For Ex-zone gas	None
For Ex-zone dust	None	Cover model	Blind cover	Circuit integrity	None
Equipped with	None	Shape	Rectangular	Number of inlets	10
Inlet from the rear	No	Transparent cover	No	Connectable	No
For tube diameter	32 mm	Mounting in the soil	No	Mounting under water	No
Type of housing feed-through	Trimmable step membrane	Cover attachment	Screwed	Castable	No
Casting compound included	No	Sealable	No	With screening	No
Weatherproof	Yes				

Documentation available for download



Barcode



8032636761101

Unit

1 NR

0.44 [kg]



8057711599776

Cardboard

25 NR

0.605x0.4x0.36 [m]

11 [kg]