

EC410C3

SMOOTH SIDED BOX IP44 DIM. 80X80X40

Enclosures > Wall-mount > Wall-mount junction boxes > Series 410 - smooth sides > Wall mount junction boxes > Ip56 - halogen free



Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-22

Description

Junction box with smooth walls and pre-drilled holes. Manufactured in shockproof, UV-resistant, and halogen-free technopolymer (ABS-based). Impact resistance rating IK08. Glow Wire Test (GWT) resistance up to 650°C. Snap-on pressure lid, tool-free assembly. Double insulation capability via optional plugs. Rear central thread for wall mounting using threaded anchors. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2006 standards. Installation temperature range: minimum -5°C, maximum +60°C. Operating temperature range: minimum -25°C, maximum +70°C. Protection degree IP44.

Dimensions: 80x80x40 mm

6 pre-drilled inlets for 20 mm diameter conduits

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Rated insulation voltage Ui	400 V	Mounting method	Wall-/ceiling mounting	Degree of protection (IP)	IP44
Material	Plastic	Halogen free	Yes	Surface protection	Untreated
Colour	Grey	Width	80 mm	Depth	40 mm
Model	Junction box	Length	80 mm	Diameter	0 mm
Working temperature	-25-70 °C	Explosion-tested version	No	For Ex-zone gas	None
For Ex-zone dust	None	Cover model	Blind cover	Circuit integrity	None
Equipped with	None	Shape	Square	Number of inlets	6
Inlet from the rear	No	Transparent cover	No	Connectable	No
For tube diameter	20 mm	Mounting in the soil	No	Mounting under water	No
Type of housing feed-through	Preembossing	Cover attachment	Snapped on	Castable	Yes
Casting compound included	No	Sealable	No	With screening	No
Weatherproof	Yes				

Documentation available for download



Barcode



8050880881475

Pack

5 NR

0.3185 [kg]



8057711590131

Cardboard

150 NR

0.605x0.4x0.35 [m]

9.555 [kg]