EC60004

WALL-MOUNT MODULAR ENCLOSURE IP40 DIM.150X170X100 4 MOD. GREY TRANSP.DOOR

Enclosures > Wall-mount > Wall modular enclosures > Series 600 - ip40 modular enclosures > Small distribution board > Grey

Technical Symbols/Marks/Approvals

IP40	GWT 650°	☐	CE	RoHS II	⊌	MADE IN ITALY

Norms

EN 60670-1   EN 60670-24

Description

Wall-mounted consumer unit. Made of shock-resistant, UV-resistant, and halogen-free ABS-based technopolymer. Impact resistance rating: IK08. Resistance to abnormal heat up to 650°C (Glow Wire Test - GWT). Halogen-free ABS-based technopolymer base and cover. Reversible cover. Smoked polycarbonate door. Self-adhesive circuit identification label included. Blanking plates for unused modules included. Fixing screw caps provided to maintain IP protection rating and double insulation. Galvanized steel DIN rail installed. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperatures: minimum –5°C, maximum +60°C. Operating temperatures: minimum -25°C, maximum +70°C. Protection degree: IP40.
External dimensions: 150x170x100 mm
4 DIN modules
Dissipable power: 11 W

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board

Mounting method	Surface mounted	**Degree of protection (IP)**	IP40	**Width in number of modular spacings**	4
Colour	Grey	**Width**	150 mm	**Height**	170 mm
Depth	100 mm	**RAL-number**	7035	**UV resistant**	Yes
Type of covering	Door	**Type of door**	Single	**Transparent cover/door**	Yes
With lock	No	**Inner depth**	100 mm	**Number of rows**	1
Extension possible	No	**Housing material**	Plastic	**With mounting plate**	No
Signal passing door	No	**Type of closure**	Other	**Earthing terminal block**	No
Neutral terminal block	No	**DIN-rail**	Yes	**EMC-version**	No

Technical Characteristics

dimensions	150x170x100 mm	**Power dissipation**	11 W

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

16/05/2026 - 1/2

Documentation available for download

Instruction booklet

Istruzioni 600-610_0423.pdf

Certification

Serie 600-610 IMQ_CA02.00428_2018.pdf

Dimensions and technical drawings

EC60004_2025.pdf

Barcode

8032636762641
Unit
1 NR
0.165x0.175x0.105 [m]
0.5227 [kg]

8059307210010
Cardboard
22 NR
0.605x0.4x0.35 [m]
11.4994 [kg]