

**EC60024B**

**WALL-MOUNT MODULAR ENCLOSURE IP40  
DIM.280X350X100 24 MOD. WHITE TRAN.DOOR**



Enclosures > Wall-mount > Wall modular enclosures > Series 600 - ip40 modular enclosures > Small distribution board > White

**Technical Symbols/Marks/Approvals**



**Norms**

EN 60670-1 EN 60670-24

**Description**

Wall-mounted consumer unit. Made of shockproof UV-resistant and halogen-free ABS-based technopolymer. Impact resistance rating IK08. Resistance to abnormal heat up to 650°C (GWT). Base and cover in halogen-free ABS-based technopolymer. Reversible cover. Smoked polycarbonate door. Self-adhesive circuit identification label included. Blanking plates for unused modules included. Fixing screw caps provided to maintain IP protection rating and double insulation. Mounted galvanized steel DIN rail. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperatures: minimum -5°C, maximum +60°C. Operating temperatures: minimum -25°C, maximum +70°C. IP40 protection rating.

External dimensions 280x350x100 mm

24 DIN modules (2x12)

Power dissipation 30 W

**Etim**

**GROUP EG000023 - Distribution boards**

**CLASS EC000214 - Small distribution board**

<b>Mounting method</b>	Surface mounted	<b>Degree of protection (IP)</b>	IP40	<b>Width in number of modular spacings</b>	24
<b>Colour</b>	White	<b>Width</b>	280 mm	<b>Height</b>	350 mm
<b>Depth</b>	100 mm	<b>RAL-number</b>	9001	<b>UV resistant</b>	Yes
<b>Type of covering</b>	Door	<b>Type of door</b>	Single	<b>Transparent cover/door</b>	Yes
<b>With lock</b>	No	<b>Inner depth</b>	100 mm	<b>Number of rows</b>	2
<b>Extension possible</b>	No	<b>Housing material</b>	Plastic	<b>With mounting plate</b>	No
<b>Signal passing door</b>	No	<b>Type of closure</b>	Other	<b>Earthing terminal block</b>	No
<b>Neutral terminal block</b>	No	<b>DIN-rail</b>	Yes	<b>EMC-version</b>	No

**Technical Characteristics**

<b>dimensions</b>	280x350x100 mm	<b>Power dissipation</b>	30 W
-------------------	----------------	--------------------------	------

## Documentation available for download

### Instruction booklet



Istruzioni 600-610\_0423.pdf

### Certification



Serie 600-610  
IMQ\_CA02.00428\_2018.pdf

## Dimensions and technical drawings



EC60024\_2025.pdf

## Barcode



8032636762740

### Unit

1 NR

0.33x0.41x0.16 [m]

1.797 [kg]