

EC60072B



**WALL-MOUNT MOD. ENCL. IP40 420X885X150 mm 72
MOD. WHITE TRANSP. DOOR**

Enclosures > Wall-mount > Wall modular enclosures > Series 600 - ip40 modular enclosures > Small distribution board > White

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Description

Wall-mounted consumer unit. Made of shockproof UV-resistant and halogen-free ABS-based technopolymer. Impact resistance rating IK08. Resistance to abnormal heat up to 650°C (GWT). Base and cover in halogen-free ABS-based technopolymer. Reversible cover. Smoked polycarbonate door. Self-adhesive circuit identification label included. Blanking plates for unused modules included. Fixing screw caps provided to maintain IP protection rating and double insulation. Mounted galvanized steel DIN rail. Adjustable to two heights. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperatures: minimum – 5°C, maximum +60°C. Operating temperatures: minimum -25°C, maximum +70°C. IP40 protection rating.

External dimensions 420x885x150 mm
Adjustable window pitch / DIN rail pitch 150-175-200 mm
72 DIN modules (4x18)
Power dissipation 85 W

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board

Mounting method	Surface mounted	Degree of protection (IP)	IP40	Width in number of modular spacings	72
Colour	White	Width	420 mm	Height	885 mm
Depth	150 mm	RAL-number	9001	UV resistant	Yes
Type of covering	Door	Type of door	Double	Transparent cover/door	Yes
With lock	No	Inner depth	150 mm	Number of rows	4
Extension possible	No	Housing material	Plastic	With mounting plate	No
Signal passing door	No	Type of closure	Other	Earthing terminal block	No
Neutral terminal block	No	DIN-rail	Yes	EMC-version	No

Technical Characteristics

dimensions

420x885x150 mm

Power dissipation

85 W

Documentation available for download

Instruction booklet




Istruzioni 600-610_0423.pdf

Certification



Serie 600-610
IMQ_CA02.00428_2018.pdf

Dimensions and technical drawings

 EC62072_2025.pdf

Barcode



8054382041122

Unit

1 NR

0.9x0.47x0.165 [m]

7.5 [kg]