

## EC61054

### WALL-MOUNT MODULAR ENCLOSURE IP40 DIM.400X600X130 54 MOD. GREY W/O DOOR

Enclosures > Wall-mount > Wall modular enclosures > Series 610 - ip40 modular enclosures without door > Small distribution board > Grey



#### Technical Symbols/Marks/Approvals



#### Norms

EN 60670-1 EN 60670-24

## Description

Wall-mounted consumer unit. Made of shockproof UV-resistant and halogen-free ABS-based technopolymer. Impact resistance rating IK08. Resistance to abnormal heat up to 650°C (GWT). Base and cover in halogen-free ABS-based technopolymer. Reversible cover. Self-adhesive circuit identification label included. Blanking plates for unused modules included. Fixing screw caps provided to maintain IP protection rating and double insulation. Mounted galvanized steel DIN rail. Adjustable to two heights. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperatures: minimum -5°C, maximum +60°C. Operating temperatures: minimum -25°C, maximum +70°C. IP40 protection rating. The IP40 protection rating (impossibility of inserting a Ø 1 mm test wire) is achieved by installing accessories with IP40 protection rating, devices with a smooth front surface or with blanking plates. External dimensions 400x600x130 mm

54 DIN modules (3x18)  
Power dissipation 79 W

## Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board

<b>Mounting method</b>	Surface mounted	<b>Degree of protection (IP)</b>	IP40	<b>Width in number of modular spacings</b>	54
<b>Colour</b>	Grey	<b>Width</b>	400 mm	<b>Height</b>	600 mm
<b>Depth</b>	130 mm	<b>RAL-number</b>	7035	<b>UV resistant</b>	Yes
<b>Type of covering</b>	None	<b>Type of door</b>	Other	<b>Transparent cover/door</b>	No
<b>With lock</b>	No	<b>Inner depth</b>	130 mm	<b>Number of rows</b>	3
<b>Extension possible</b>	No	<b>Housing material</b>	Plastic	<b>With mounting plate</b>	No
<b>Signal passing door</b>	No	<b>Type of closure</b>	Other	<b>Earthing terminal block</b>	No
<b>Neutral terminal block</b>	No	<b>DIN-rail</b>	Yes	<b>EMC-version</b>	No

## Technical Characteristics

**dimensions**

400x600x130 mm

**Power dissipation**

79 W

## Documentation available for download

### Instruction booklet



Istruzioni 600-610\_0423.pdf

### Certification



Serie 600-610  
IMQ\_CA02.00428\_2018.pdf

## Dimensions and technical drawings



EC61054\_2025.pdf

## Barcode



8032636763044

**Unit**

1 NR

4 [kg]