

EC62004

WALL-MOUNT MOD.ENCL. IP65 150x170x100mm 4 MOD. GREY



Enclosures > Wall-mount > Wall modular enclosures > Series 620 - ip65 modular enclosures > Small distribution board > Grey

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Description

Wall-mounted consumer unit. Made of shockproof UV-resistant and halogen-free ABS-based technopolymer. Impact resistance rating IK08. Resistance to abnormal heat up to 650°C (GWT). Base and cover in halogen-free ABS-based technopolymer. Reversible cover. Smoked polycarbonate door. Cylinder safety lock installation possible. Door closure with spring-loaded sliding inserts. Self-adhesive circuit identification label included. Blanking plates for unused modules included. Fixing screw caps provided to maintain IP protection rating and double insulation. Mounted galvanized steel DIN rail. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperatures: minimum -5°C, maximum +60°C. Operating temperatures: minimum -25°C, maximum +70°C. IP65 protection rating.

External dimensions 150x170x100 mm

4 DIN modules

Power dissipation 10 W

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board

| | | | | | |
|-------------------------------|-----------------|----------------------------------|---------|--|--------|
| Mounting method | Surface mounted | Degree of protection (IP) | IP65 | Width in number of modular spacings | 4 |
| Colour | Grey | Width | 150 mm | Height | 170 mm |
| Depth | 100 mm | RAL-number | 7035 | UV resistant | Yes |
| Type of covering | Door | Type of door | Single | Transparent cover/door | Yes |
| With lock | No | Inner depth | 100 mm | Number of rows | 1 |
| Extension possible | No | Housing material | Plastic | With mounting plate | No |
| Signal passing door | No | Type of closure | Other | Earthing terminal block | No |
| Neutral terminal block | No | DIN-rail | Yes | EMC-version | No |

Technical Characteristics

dimensions

150x170x100 mm

Power dissipation

10 W

Documentation available for download

Instruction booklet



Istruzioni
620_0423.pdf

Certification



Serie 620
IMQ_CA02.00788_
2018.pdf

Dimensions and technical drawings

 EC62004_2025.pdf

Barcode



8032636763068

Unit

1 NR

0.165x0.175x0.105 [m]

0.6136 [kg]



8059307210164

Cardboard

22 NR

0.605x0.4x0.35 [m]

13.4992 [kg]