

**EC62008**

**WALL-MOUNT MOD.ENCL. IP65 200x180x100mm 8 MOD. GREY**



Enclosures > Wall-mount > Wall modular enclosures > Series 620 - ip65 modular enclosures > Small distribution board > Grey

**Technical Symbols/Marks/Approvals**



**Norms**

EN 60670-1 EN 60670-24

**Description**

Wall-mounted consumer unit. Made of shockproof UV-resistant and halogen-free ABS-based technopolymer. Impact resistance rating IK08. Resistance to abnormal heat up to 650°C (GWT). Base and cover in halogen-free ABS-based technopolymer. Reversible cover. Smoked polycarbonate door. Cylinder safety lock installation possible. Door closure with spring-loaded sliding inserts. Self-adhesive circuit identification label included. Blanking plates for unused modules included. Fixing screw caps provided to maintain IP protection rating and double insulation. Mounted galvanized steel DIN rail. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperatures: minimum -5°C, maximum +60°C. Operating temperatures: minimum -25°C, maximum +70°C. IP65 protection rating.

External dimensions 200x180x100 mm  
8 DIN modules  
Power dissipation 13 W

**Etim**

**GROUP EG000023 - Distribution boards**

**CLASS EC000214 - Small distribution board**

<b>Mounting method</b>	Surface mounted	<b>Degree of protection (IP)</b>	IP65	<b>Width in number of modular spacings</b>	8
<b>Colour</b>	Grey	<b>Width</b>	200 mm	<b>Height</b>	180 mm
<b>Depth</b>	100 mm	<b>RAL-number</b>	7035	<b>UV resistant</b>	Yes
<b>Type of covering</b>	Door	<b>Type of door</b>	Single	<b>Transparent cover/door</b>	Yes
<b>With lock</b>	No	<b>Inner depth</b>	100 mm	<b>Number of rows</b>	1
<b>Extension possible</b>	No	<b>Housing material</b>	Plastic	<b>With mounting plate</b>	No
<b>Signal passing door</b>	No	<b>Type of closure</b>	Other	<b>Earthing terminal block</b>	No
<b>Neutral terminal block</b>	No	<b>DIN-rail</b>	Yes	<b>EMC-version</b>	No

## Technical Characteristics

**dimensions**

200x180x100 mm

**Power dissipation**

13 W

## Documentation available for download

### Instruction booklet



Istruzioni  
620\_0423.pdf

### Certification



Serie 620  
IMQ\_CA02.00788\_  
2018.pdf

## Dimensions and technical drawings



EC62008\_2025.pdf

## Barcode



8032636763082

### Unit

1 NR

0.19x0.205x0.105 [m]

0.7857 [kg]



8059307210171

### Cardboard

14 NR

0.605x0.4x0.35 [m]

10.9998 [kg]