

ECICTA20N-UV



**UV HF ICTA PLIABLE PP CONDUIT
34223 Ø20 mm - 100 m - BLACK**

Conduits and fittings > Conduits > Corrugated conduits > Series icta - pp - class 34223 - 750 n - uv > plastic conduits > Black



Technical Symbols/Marks/Approvals

HF			GWT 850°	+90°	CE	RoHS II	MADE IN ITALY
----	--	--	----------	------	----	---------	---------------

Norms

EN 61386-1 EN 61386-22 EN 61034-2 EN 50642

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polypropylene (PP)	Halogen free	Yes
Colour	Black	RAL-number	9005	UV resistant	Yes
Suitable for underground installation	No	Operating temperature	-5-90 °C	Bending strength	Pliable, self recovering
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Heavy (class 4 / 6 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	Yes	Suitable for installation on wood	Yes
Suitable for hollow wall installation	Yes	Suitable for concrete installation	Yes	Machine and systems installation	No
Suitable for underfloor installation (screed)	Yes	Suitable for outdoor installation	Yes	Inner diameter	13.5 mm
Outer diameter	20 mm	High conducting inner coating	Yes	With metre indication	No

Barcode



8055035965543

Cardboard

100 MT

0.51x0.51x0.24 [m]

6.5 [kg]



8055035965550

Pallet

5000 MT

0.8x1.2x2.5 [m]

325 [kg]