

EC625002R



SPARE BLANK DOOR 325X430 mm

Enclosures > Wall-mount > Grp enclosures > Accessories > Accessories for distribution board > Spare blank door



Technical Symbols/Marks/Approvals

IP66	GWT 960°	UL94 V0	IK10	HF		CE	RoHS II
	MADE IN ITALY						

Norms

EN 62208

Description

Replacement door for polyester enclosures. Manufactured in glass-fiber reinforced thermosetting polyester. Halogen Free. Self-extinguishing V0 according to UL-94. UV resistant. Impact resistance rating IK10. Glow Wire Test (GWT) resistance up to 960°C. Installation temperature range: minimum -25°C, maximum +60°C. Rated operational voltage 1000 VAC, 1500 VDC, suitable for photovoltaic applications. Manufactured in compliance with standards EN 62208:2011, EN 60695-2-11:2000/2001, IEC 60754-1:2001/AMD1:2019, IEC 60754-2:2011/AMD1:2019, IEC 60754-3:2018. Protection degree IP66. External dimensions: 325x430x22 mm

Etim

GROUP EG000011 - Enclosures/cabinets

CLASS EC002620 - Components for installation (enclosure/cabinet)

Material	Other	Colour	Grey	Width	325 mm
Height	430 mm	Depth	22 mm	Model	Other
RAL-number	7035	Suitable for enclosure building width	325 mm	Suitable for enclosure building height	430 mm
Suitable for enclosure building depth	185 mm				

Documentation available for download



Certification
Serie 625
IMQ_CA02.06897_
2024.pdf



Brochure
Quadri Poliestere
IT.pdf



Brochure
Quadri
Poliestere_ENG.pdf

Barcode



8053676579983
Unit
1 NR
0.95 [kg]