

**EC625005R**



**SPARE BLANK DOOR 545X655 mm**

Enclosures > Wall-mount > Grp enclosures > Accessories > Accessories for distribution board > Spare blank door



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

**Technical Symbols/Marks/Approvals**

IP66	GWT 960°	UL94 V0	IK10	HF		CE	RoHS II
	MADE IN ITALY						

**Norms**

EN 62208

**Description**

Replacement door for polyester enclosures. Manufactured in glass-fiber reinforced thermosetting polyester. Halogen Free. Self-extinguishing V0 according to UL-94. UV resistant. Impact resistance rating IK10. Glow Wire Test (GWT) resistance up to 960°C. Installation temperature range: minimum -25°C, maximum +60°C. Rated operational voltage 1000 VAC, 1500 VDC, suitable for photovoltaic applications. Manufactured in compliance with standards EN 62208:2011, EN 60695-2-11:2000/2001, IEC 60754-1:2001/AMD1:2019, IEC 60754-2:2011/AMD1:2019, IEC 60754-3:2018. Protection degree IP66. External dimensions: 545x655x22 mm

**Etim**

**GROUP EG000011 - Enclosures/cabinets**

**CLASS EC002620 - Components for installation (enclosure/cabinet)**

<b>Material</b>	Other	<b>Colour</b>	Grey	<b>Width</b>	545 mm
<b>Height</b>	655 mm	<b>Depth</b>	22 mm	<b>Model</b>	Other
<b>RAL-number</b>	7035	<b>Suitable for enclosure building width</b>	545 mm	<b>Suitable for enclosure building height</b>	655 mm
<b>Suitable for enclosure building depth</b>	265 mm				

## Documentation available for download



**Certification**  
Serie 625  
IMQ\_CA02.06897\_  
2024.pdf



**Brochure**  
Quadri Poliestere  
IT.pdf



**Brochure**  
Quadri  
Poliestere\_ENG.pdf

## Barcode



8054382041030  
**Unit**  
1 NR  
1.65 [kg]