

EC625005R

SPARE BLANK DOOR 545X655 mm

Enclosures > Wall-mount > Grp enclosures > Accessories > Accessories for distribution board > Spare blank door

Technical Symbols/Marks/Approvals

IP66 | GWT 960° | UL94 V0 | IK10 | HF | RoHS II | MADE IN ITALY

Norms

EN 62208

Description

Replacement door for polyester enclosures. Manufactured in glass-fiber reinforced thermosetting polyester. Halogen Free. Self-extinguishing V0 according to UL-94. UV resistant. Impact resistance rating IK10. Glow Wire Test (GWT) resistance up to 960°C. Installation temperature range: minimum –25°C, maximum +60°C. Rated operational voltage 1000 VAC, 1500 VDC, suitable for photovoltaic applications. Manufactured in compliance with standards EN 62208:2011, EN 60695-2-11:2000/2001, IEC 60754-1:2001/AMD1:2019, IEC 60754-2:2011/AMD1:2019, IEC 60754-3:2018. Protection degree IP66.
External dimensions: 545x655x22 mm

Etim

GROUP EG000011 - Enclosures/cabinets

CLASS EC002620 - Components for installation (enclosure/cabinet)

Material	Other	**Colour**	Grey	**Width**	545 mm
Height	655 mm	**Depth**	22 mm	**Model**	Other
RAL-number	7035	**Suitable for enclosure building width**	545 mm	**Suitable for enclosure building height**	655 mm
Suitable for enclosure building depth	265 mm				

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

Serie 625 IMQ_CA02.06897_2024.pdf



Brochure

Quadri Poliestere IT.pdf



Brochure

Quadri Poliestere_ENG.pdf

Barcode

8054382041030

Unit

1 NR

1.65 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.