

## EC625011



### GRP POLYESTER ENCLOSURE TRANSPARENT DOOR 270X305X170 mm



Enclosures > Wall-mount > Grp enclosures > Boards >  
Distribution board > Transparent window door

#### Technical Symbols/Marks/Approvals



#### Norms

EN 62208

## Description

Wall-mounted distribution board. Made of glass-fiber reinforced thermosetting polyester. Halogen Free. Self-extinguishing V0 rating according to UL-94. Transparent polycarbonate window. UV resistant. Impact resistance rating IK10. Glow wire test (GWT) resistance up to 960°C. Installation temperature range: minimum -25°C, maximum +60°C.

Rated operational voltage 1000 VAC, 1500 VDC, suitable for photovoltaic applications. Double insulation. Adjustable DIN rails to accommodate circuit breakers with heights of 48-75-102 mm. Reversible door opening over 180° with stainless steel pins. Security cylinder lock compatible. Blanking covers for unused modules included. Screw caps provided to maintain IP rating and double insulation.

Manufactured in accordance with EN 62208:2011, EN 60695-2-11:2000/2001, IEC60754-1:2001/AMD1:2019, IEC60754-2:2011/AMD1:2019, IEC60754-3:2018. Protection degree IP66.

External dimensions 270x305x170 mm


**Etim**

**GROUP EG000011 - Enclosures/cabinets**  
**CLASS EC000261 - Enclosure/cabinet (empty)**


<b>Degree of protection (IP)</b>	IP66	<b>Material</b>	Other	<b>Material quality</b>	GRP (Glass fibre reinforced plastic)
<b>Surface finishing</b>	Untreated	<b>Colour</b>	Grey	<b>Impact strength</b>	IK10
<b>Width</b>	270 mm	<b>Height</b>	305 mm	<b>Depth</b>	170 mm
<b>With cover</b>	Yes	<b>RAL-number</b>	7035	<b>With mounting plate</b>	No
<b>Pre-stamping</b>	No	<b>EMC-version</b>	No	<b>Suitable for wall mounting</b>	Yes
<b>Couplable</b>	Yes	<b>Mounting plate depth-adjustable</b>	Yes	<b>Suitable for wall built-in</b>	No
<b>Pole fastening</b>	Yes	<b>With door</b>	Yes	<b>Number of doors</b>	1
<b>With glazed door</b>	Yes	<b>With ventilation door</b>	No	<b>With rear door</b>	No
<b>Number of locks</b>	1	<b>Transparent cover</b>	No	<b>Suitable for outdoor set-up</b>	Yes
<b>Pitched roof</b>	No	<b>Number of connector holes</b>	0	<b>Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890</b>	16 W
<b>Max. permitted load of the mounting plate according to IEC 62208</b>	10 kg				

**Documentation available for download**

**Instruction booklet**  
Istruzioni\_625\_042 3.pdf



**Certification**  
MI22-0079305-01a - ELETTROCANALI SPA - HCI\_1 - TR\_625.pdf



**Certification**  
MI22-0079305-01b - ELETTROCANALI SPA - pH - TR\_625.pdf



**Certification**  
MI22-0079305-01c - ELETTROCANALI SPA - HCI\_3 - TR\_625.pdf



**Certification**  
MI22-0079343-01\_TR\_625.pdf



**Certification**  
Serie 625 IMQ\_CA02.06897\_2024.pdf



**Brochure**  
Quadri Poliestere IT.pdf



**Brochure**  
Quadri Poliestere\_ENG.pdf



## Barcode



8053676570416

**Unit**

1 NR

0.39x0.295x0.21 [m]

3.2 [kg]