

EC625025



**POLYESTER INTERNAL DOOR
487X597 mm**

Enclosures > Wall-mount > Grp enclosures > Accessories > Accessories for distribution board > Internal fibre-glass door



Technical Symbols/Marks/Approvals

| | | | | | | | |
|------|---------------------|------------|------|----|--|----|---------|
| IP66 | GWT 960° | UL94 V0 | IK10 | HF | | CE | RoHS II |
| | MADE IN ITALY | | | | | | |

Norms

EN 62208

Description

Internal door for polyester enclosures with stainless steel metal pins. Dual-level installation. Manufactured in glass-fiber reinforced thermosetting polyester. Halogen Free. Self-extinguishing V0 according to UL-94. UV resistant. Impact resistance rating IK10. Glow Wire Test (GWT) resistance up to 960°C. Installation temperature range: minimum -25°C, maximum +60°C. Rated operational voltage 1000 VAC, 1500 VDC, suitable for photovoltaic applications. Manufactured in compliance with standards EN 62208:2011, EN 60695-2-11:2000/2001, IEC 60754-1:2001/AMD1:2019, IEC 60754-2:2011/AMD1:2019, IEC 60754-3:2018. Protection degree IP66. External dimensions: 487x597x19 mm

Etim

GROUP EG000011 - Enclosures/cabinets

CLASS EC002620 - Components for installation (enclosure/cabinet)

| | | | | | |
|--|--------|--|--------|---|--------|
| Material | Other | Colour | Grey | Width | 487 mm |
| Height | 597 mm | Depth | 19 mm | Model | Other |
| RAL-number | 7035 | Suitable for enclosure building width | 545 mm | Suitable for enclosure building height | 655 mm |
| Suitable for enclosure building depth | 265 mm | | | | |

Documentation available for download



Certification
Serie 625
IMQ_CA02.06897_
2024.pdf



Brochure
Quadri Poliestere
IT.pdf



Brochure
Quadri
Poliestere_ENG.pdf

Barcode



8053676570515
Unit
1 NR
1.7 [kg]