

**EC625041**



**INSULATING BACK PLATE 207X239 mm**

Enclosures > Wall-mount > Grp enclosures > Accessories > Accessories for distribution board > Insulating back plate



**Technical Symbols/Marks/Approvals**

IP66	GWT 960°	UL94 V0	IK10	HF		CE	RoHS II
	MADE IN ITALY						

**Norms**

EN 62208

**Description**

Insulating mounting plate for polyester enclosures. Paper-based phenolic resin laminate. Can be installed directly on the back or at different levels using an optional adjustment kit. Breakdown voltage 30 kV. Dielectric strength 1 kV/mm. External dimensions: 207x239x4 mm

**Etim**

**GROUP EG000011 - Enclosures/cabinets**

**CLASS EC002620 - Components for installation (enclosure/cabinet)**

<b>Material</b>	Other	<b>Colour</b>	White	<b>Width</b>	207 mm
<b>Height</b>	239 mm	<b>Depth</b>	4 mm	<b>Model</b>	Other
<b>RAL-number</b>	7035	<b>Suitable for enclosure building width</b>	270 mm	<b>Suitable for enclosure building height</b>	305 mm
<b>Suitable for enclosure building depth</b>	170 mm				

**Technical Characteristics**

thickness 4 mm

## Documentation available for download



**Certification**  
Serie 625  
IMQ\_CA02.06897\_  
2024.pdf



**Brochure**  
Quadri Poliestere  
IT.pdf



**Brochure**  
Quadri  
Poliestere\_ENG.pdf

## Barcode



8053676570614  
**Unit**  
1 NR  
0.4 [kg]