

EC625042

INSULATING BACK PLATE 264X364 mm

Enclosures > Wall-mount > Grp enclosures > Accessories > Accessories for distribution board > Insulating back plate

Technical Symbols/Marks/Approvals

IP66 | GWT 960° | UL94 V0 | IK10 | HF | RoHS II | MADE IN ITALY

Norms

EN 62208

Description

Insulating mounting plate for polyester enclosures. Paper-based phenolic resin laminate. Can be installed directly on the back or at different levels using an optional adjustment kit. Breakdown voltage 30 kV. Dielectric strength 1 kV/mm.
External dimensions: 264x364x4 mm

Etim

GROUP EG000011 - Enclosures/cabinets

CLASS EC002620 - Components for installation (enclosure/cabinet)

Material	Other	**Colour**	White	**Width**	264 mm
Height	364 mm	**Depth**	4 mm	**Model**	Other
RAL-number	7035	**Suitable for enclosure building width**	325 mm	**Suitable for enclosure building height**	430 mm
Suitable for enclosure building depth	185 mm				

Technical Characteristics

thickness	4 mm

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

Serie 625 IMQ_CA02.06897_2024.pdf



Brochure

Quadri Poliestere IT.pdf



Brochure

Quadri Poliestere_ENG.pdf

Barcode

8053676570621

Unit

1 NR

0.6 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.