

EC625045



INSULATING BACK PLATE 482X589 mm

Enclosures > Wall-mount > Grp enclosures > Accessories > Accessories for distribution board > Insulating back plate



Technical Symbols/Marks/Approvals

IP66	GWT 960°	UL94 V0	IK10	HF		CE	RoHS II
	MADE IN ITALY						

Norms

EN 62208

Description

Insulating mounting plate for polyester enclosures. Paper-based phenolic resin laminate. Can be installed directly on the back or at different levels using an optional adjustment kit. Breakdown voltage 30 kV. Dielectric strength 1 kV/mm. External dimensions: 482x589x4 mm

Etim

GROUP EG000011 - Enclosures/cabinets

CLASS EC002620 - Components for installation (enclosure/cabinet)

Material	Other	Colour	White	Width	482 mm
Height	589 mm	Depth	4 mm	Model	Other
RAL-number	7035	Suitable for enclosure building width	545 mm	Suitable for enclosure building height	655 mm
Suitable for enclosure building depth	265 mm				

Technical Characteristics

thickness 4 mm

Documentation available for download



Certification
Serie 625
IMQ_CA02.06897_
2024.pdf



Brochure
Quadri Poliestere
IT.pdf



Brochure
Quadri
Poliestere_ENG.pdf

Barcode



8053676570652
Unit
1 NR
1.7 [kg]