

**EC63012C**



**FLUSH MOUNT.MOD.ENCLOSURE IP40  
DIM.320X240X80 12 MOD. WHITE  
SOLID DOOR**



Enclosures > Recessed > Recessed modular enclosures > Series 630 - masonry modular enclosures > Small distribution board > White - blank door

**Technical Symbols/Marks/Approvals**



**Norms**

EN 60670-1 EN 60670-24

**Etim**

**GROUP EG000023 - Distribution boards**

**CLASS EC000214 - Small distribution board**

<b>Mounting method</b>	Flush-mounted	<b>Degree of protection (IP)</b>	IP40	<b>Width in number of modular spacings</b>	12
<b>Built-in depth</b>	80 mm	<b>Colour</b>	White	<b>Width</b>	320 mm
<b>Height</b>	240 mm	<b>Depth</b>	100 mm	<b>Built-in height</b>	80 mm
<b>RAL-number</b>	9001	<b>Type of covering</b>	Door	<b>Type of door</b>	Single
<b>Transparent cover/door</b>	No	<b>With lock</b>	No	<b>Inner depth</b>	80 mm
<b>Number of rows</b>	1	<b>Extension possible</b>	No	<b>Housing material</b>	Plastic
<b>With mounting plate</b>	No	<b>Type of closure</b>	Other	<b>Earthing terminal block</b>	No
<b>Neutral terminal block</b>	No	<b>DIN-rail</b>	Yes	<b>EMC-version</b>	No

**Technical Characteristics**

<b>dimensions</b>	320x240x80 mm	<b>Power dissipation</b>	25 W
-------------------	---------------	--------------------------	------

## Documentation available for download

 <p><b>Instruction booklet</b> Istruzioni 630-635_0125_0125.pdf</p>	 <p><b>Certification</b> Serie 630 IMQ_CA02.01745_2020.pdf</p>
--	---

## Dimensions and technical drawings

 EC63012\_2025.pdf

## Barcode

 <p>8032793873099 <b>Unit</b> 1 NR 1.1429 [kg]</p>	 <p>8059307214582 <b>Cardboard</b> 7 NR 0.41x0.605x0.365 [m] 8.0003 [kg]</p>
---	---