

EC63036BE

FLUSH MOUNT.MOD.ENCLOSURE IP40 DIM.430X410X80 36 MOD. WHITE (2X18 T.B.)



Enclosures > Recessed > Recessed modular enclosures >
Series 630 - masonry modular enclosures > Small distribution
board > White -transparent door - equipped

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Description

Flush-mounting distribution board for masonry walls. Base made of high-impact technopolymer with low smoke emission. Resistance to abnormal heat up to 650°C (GWT). Halogen-free ABS technopolymer cover. Reversible cover. Smoked polycarbonate door. Option to install a cylinder safety lock. Door closure with spring-loaded sliding inserts. High-gloss finish on outer frame and door. Self-adhesive circuit identification labels included. Blanking covers for unused modules included. Galvanized steel DIN rail mounted on a removable and adjustable support for perfect horizontal alignment. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperature range: minimum -15°C, maximum +60°C. IP40 protection degree.

External dimensions 430x410 mm

Base depth 80 mm

36 DIN modules (2x18)

4 terminal blocks 6x10 mm - 12 holes

4 terminal blocks 6x10 mm - 8 holes

Dissipated power 52 W

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board

Mounting method	Flush-mounted	Degree of protection (IP)	IP40	Width in number of modular spacings	36
Built-in depth	80 mm	Colour	White	Width	430 mm
Height	410 mm	Depth	100 mm	Built-in height	80 mm
RAL-number	9001	Type of covering	Door	Type of door	Single
Transparent cover/door	Yes	With lock	No	Inner depth	80 mm
Number of rows	2	Extension possible	No	Housing material	Plastic
With mounting plate	No	Type of closure	Other	Earthing terminal block	Yes
Neutral terminal block	Yes	DIN-rail	Yes	EMC-version	No

Technical Characteristics

dimensions	430x410x80 mm	Mounting equipment	2	Terminal blocks/holes	4x12 + 4x8
Power dissipation	52 W	Tipo_Morsettiera	2x16 +10x10 - 2x16+6x10 mm ²		

Documentation available for download



Instruction booklet


Istruzioni 630-635_0125_0125.pdf



Certification

Serie 630
IMQ_CA02.01745_2020.pdf

Dimensions and technical drawings



EC63036_COPERCHIO_2025.pdf



EC63036_FONDO_2025.pdf

Barcode



8053676572496

Unit

1 NR

2.717 [kg]