



EC63072N

**FLUSH MOUNT.MOD.ENCLOSURE IP40
DIM. 450X853X95 72 MOD. BLACK**



Enclosures > Recessed > Recessed modular enclosures > Series 630 - masonry modular enclosures > Small distribution board > Black -transparent door

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board


Mounting method	Flush-mounted	Degree of protection (IP)	IP40	Width in number of modular spacings	72
Built-in depth	95 mm	Colour	Black	Width	450 mm
Height	853 mm	Depth	119 mm	Built-in height	95 mm
RAL-number	7021	Type of covering	Door	Type of door	Double
Transparent cover/door	Yes	With lock	No	Inner depth	95 mm
Number of rows	4	Extension possible	No	Housing material	Plastic
With mounting plate	No	Type of closure	Other	Earthing terminal block	No
Neutral terminal block	No	DIN-rail	Yes	EMC-version	No

Technical Characteristics

dimensions	450x853x95 mm	Power dissipation	90 W
-------------------	---------------	--------------------------	------

Documentation available for download

Instruction booklet



Istruzioni 630-635_0125_0125.pdf

Certification



Serie 630
IMQ_CA02.01745_2020.pdf

Dimensions and technical drawings

EC63072_COPERCHIO_2025.pdf



EC63072_FONDO_2025.pdf

Barcode



8033576778402

Unit

1 NR

0.9x0.47x0.165 [m]

6.5 [kg]