

**EC63336C**



**FLUSH-MOUNT MOD. ENCL.  
MULTIMEDIA 36 MOD. WHITE SOLID  
DOOR**

Enclosures > Recessed > Recessed modular enclosures > Series 633-638 - multimedia modular enclosures > Small distribution board > Masonry enclosure

**Technical Symbols/Marks/Approvals**



**Norms**

EN 60670-1 EN 60670-24

**Description**

Flush-mounting QDSA distribution board for FTTH systems for masonry walls. Base made of high-impact technopolymer with low smoke emission. Resistance to abnormal heat up to 650°C (GWT). Halogen-free ABS technopolymer cover. Reversible cover. Halogen-free ABS technopolymer door. Option to install a cylinder safety lock. Door closure with spring-loaded sliding inserts. High-gloss finish on outer frame and door. Galvanized steel DIN rail mounted on a removable and adjustable support for perfect horizontal alignment. Equipped with 1 component mounting plate featuring 8 slots for keystone jacks and 2 adjustable support shelves to hold a device. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperature range: minimum -15°C, maximum +60°C. IP40 protection degree.  
External dimensions 430x410 mm  
Base depth 80 mm  
36 DIN modules (2x18)  
Dissipated power 52 W

**Etim**

**GROUP EG000023 - Distribution boards**  
**CLASS EC000214 - Small distribution board**

<b>Mounting method</b>	Flush-mounted	<b>Degree of protection (IP)</b>	IP40	<b>Width in number of modular spacings</b>	36
<b>Built-in depth</b>	80 mm	<b>Colour</b>	White	<b>Width</b>	430 mm
<b>Height</b>	410 mm	<b>Depth</b>	100 mm	<b>Built-in height</b>	80 mm
<b>RAL-number</b>	9001	<b>Type of covering</b>	Door	<b>Type of door</b>	Single
<b>Transparent cover/door</b>	No	<b>With lock</b>	No	<b>Inner depth</b>	80 mm
<b>Number of rows</b>	2	<b>Extension possible</b>	No	<b>Housing material</b>	Plastic
<b>With mounting plate</b>	No	<b>Type of closure</b>	Other	<b>Earthing terminal block</b>	No
<b>Neutral terminal block</b>	No	<b>DIN-rail</b>	Yes	<b>EMC-version</b>	No

## Technical Characteristics

**dimensions**

430x410x80 mm

**Power dissipation**

52 W

## Dimensions and technical drawings

EC63336\_COPERCHIO\_2025.pdf



EC63036\_FONDO\_2025.pdf

## Barcode



8056351666817

**Unit**

1 NR

0.42x0.45x0.16 [m]

2.717 [kg]