

EC63512B



**DRY LINING MODULAR ENCLOSURE
12 MODULES - TRANSPARENT DOOR -
RAL9001**



Enclosures > Recessed > Recessed modular enclosures > Series 635 - dry lining modular enclosures > Small distribution board > White -transparent door

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Description

Flush-mounting distribution board for lightweight walls - plasterboard or wood. Base made of blue, high-impact technopolymer with low smoke emission. Resistance to abnormal heat up to 850°C (GWT). Halogen-free ABS technopolymer cover. Reversible cover. Smoked polycarbonate door. Option to install a cylinder safety lock. Door closure with spring-loaded sliding inserts. High-gloss finish on outer frame and door. Self-adhesive circuit identification labels included. Blanking covers for unused modules included. Galvanized steel DIN rail mounted on a removable and adjustable support for perfect horizontal alignment. Base fixing to the structure via brackets. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperature range: minimum -15°C, maximum +60°C. IP40 protection degree.
External dimensions 320x240 mm
Base depth 80 mm
12 DIN modules
Dissipated power 25 W

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board

| | | | | | |
|---------------------------|---------------------------|----------------------------------|---------|--|--------|
| Mounting method | Flush-mounted/hollow wall | Degree of protection (IP) | IP40 | Width in number of modular spacings | 12 |
| Built-in depth | 80 mm | Colour | White | Width | 320 mm |
| Height | 240 mm | Depth | 100 mm | Built-in height | 80 mm |
| RAL-number | 9001 | Type of door | Single | Transparent cover/door | Yes |
| With lock | No | Inner depth | 80 mm | Number of rows | 1 |
| Extension possible | No | Housing material | Plastic | With mounting plate | No |
| Type of closure | Other | Earthing terminal block | No | Neutral terminal block | No |
| DIN-rail | Yes | EMC-version | No | | |

Technical Characteristics

dimensions

320x240x80 mm

Power dissipation

25 W

Documentation available for download

Instruction booklet



Istruzioni 630-
635_0125_0125.pdf

Dimensions and technical drawings



EC63512_2025.pdf

Barcode




8053676572809

Unit

1 NR

0.25x0.33x0.105 [m]

1.1429 [kg]



8059307214704

Cardboard

7 NR

0.605x0.4x0.35 [m]

8.0003 [kg]