

EC63524B



**DRY LINING MODULAR ENCLOSURE
24 MODULES - TRANSPARENT DOOR -
RAL9001**



Enclosures > Recessed > Recessed modular enclosures > Series 635 - dry lining modular enclosures > Small distribution board > White -transparent door

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Description

Flush-mounting distribution board for lightweight walls - plasterboard or wood. Base made of blue, high-impact technopolymer with low smoke emission. Resistance to abnormal heat up to 850°C (GWT). Halogen-free ABS technopolymer cover. Reversible cover. Smoked polycarbonate door. Option to install a cylinder safety lock. Door closure with spring-loaded sliding inserts. High-gloss finish on outer frame and door. Self-adhesive circuit identification labels included. Blanking covers for unused modules included. Galvanized steel DIN rail mounted on a removable and adjustable support for perfect horizontal alignment. Base fixing to the structure via brackets. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperature range: minimum -15°C, maximum +60°C. IP40 protection degree.
External dimensions 320x388 mm
Base depth 80 mm
24 DIN modules (2x12)
Dissipated power 35 W

Etim

GROUP EG000023 - Distribution boards
CLASS EC000214 - Small distribution board

Mounting method	Flush-mounted/hollow wall	Degree of protection (IP)	IP40	Width in number of modular spacings	24
Built-in depth	80 mm	Colour	White	Width	320 mm
Height	388 mm	Depth	100 mm	Built-in height	80 mm
RAL-number	9001	Type of door	Single	Transparent cover/door	Yes
With lock	No	Inner depth	80 mm	Number of rows	2
Extension possible	No	Housing material	Plastic	With mounting plate	No
Type of closure	Other	Earthing terminal block	No	Neutral terminal block	No
DIN-rail	Yes	EMC-version	No		

Technical Characteristics

dimensions


320x388x80 mm

Power dissipation

35 W

Documentation available for download

Instruction booklet



Istruzioni 630-
635_0125_0125.pdf

Dimensions and technical drawings



EC63518_2025.pdf

Barcode



8053676572816

Unit

1 NR

0.33x0.41x0.16 [m]

2.1 [kg]