

EC63554B

DRY LINING MODULAR ENCLOSURE 54 MODULES - TRANSPARENT DOOR - RAL9001

Enclosures > Recessed > Recessed modular enclosures > Series 635 - dry lining modular enclosures > Small distribution board > White -transparent door

Technical Symbols/Marks/Approvals

IP40 | GWT 850° | RoHS II | MADE IN ITALY

Norms

EN 60670-1 EN 60670-24

Description

Flush-mounting distribution board for lightweight walls - plasterboard or wood. Base made of blue, high-impact technopolymer with low smoke emission. Resistance to abnormal heat up to 850°C (GWT). Halogen-free ABS technopolymer cover. Reversible cover. Smoked polycarbonate door. Option to install a cylinder safety lock. Door closure with spring-loaded sliding inserts. High-gloss finish on outer frame and door. Self-adhesive circuit identification labels included. Blanking covers for unused modules included. Galvanized steel DIN rail mounted on a removable and adjustable support for perfect horizontal alignment. Base fixing to the structure via brackets. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperature range: minimum -15°C, maximum +60°C. IP40 protection degree.
External dimensions 430x618 mm
Base depth 80 mm
54 DIN modules (3x18)
Dissipated power 77 W

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Etim

GROUP EG000023 - Distribution boards


CLASS EC000214 - Small distribution board

Mounting method	Flush-mounted/hollow wall	**Degree of protection (IP)**	IP40	**Width in number of modular spacings**	54
Built-in depth	80 mm	**Colour**	White	**Width**	430 mm
Height	618 mm	**Depth**	100 mm	**Built-in width**	405 mm
Built-in height	80 mm	**RAL-number**	9001	**UV resistant**	No
Type of covering	Door	**Cover model**	With notch	**Type of door**	Single
Transparent cover/door	Yes	**With lock**	No	**Inner depth**	80 mm
Number of rows	3	**Extension possible**	No	**Housing material**	Plastic
With mounting plate	No	**Signal passing door**	No	**Type of closure**	Other
Earthing terminal block	No	**Neutral terminal block**	No	**DIN-rail**	Yes
EMC-version	No				

Technical Characteristics

dimensions	430x618x80 mm	**Power dissipation**	77 W

Documentation available for download



Instruction booklet

Istruzioni 630-635_0125_0125.pdf



Certification

Serie 630_635 IMQ_CA02.07187_2026.pdf

Dimensions and technical drawings

EC63554_COPERCHIO_2025.pdf

EC63554_FONDO_2025.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8054382041931

Unit

1 NR

4 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.