

EC63836C

FLUSH-MOUNT MOD. ENCL. MULTIMEDIA 36 MOD. WHITE SOLID DOOR HOLLOW WALLS



Enclosures > Recessed > Recessed modular enclosures > Series 633-638 - multimedia modular enclosures > Small distribution board > Dry lining enclosure

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Description

Flush-mounting QDSA distribution board for FTTH systems for lightweight walls - plasterboard or wood. Base made of blue, high-impact technopolymer with low smoke emission. Resistance to abnormal heat up to 850°C (GWT). Halogen-free ABS technopolymer cover. Reversible cover. Halogen-free ABS technopolymer door. Option to install a cylinder safety lock. Door closure with spring-loaded sliding inserts. High-gloss finish on outer frame and door. Galvanized steel DIN rail mounted on a removable and adjustable support for perfect horizontal alignment. Equipped with 1 component mounting plate featuring 8 slots for keystone jacks and 2 adjustable support shelves to hold a device. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperature range: minimum -15°C, maximum +60°C. IP40 protection degree.

External dimensions 430x410 mm

Base depth 80 mm

36 DIN modules (2x18)

Dissipated power 52 W

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board

Mounting method	Flush-mounted/hollow wall	Degree of protection (IP)	IP40	Width in number of modular spacings	36
Built-in depth	80 mm	Colour	White	Width	430 mm
Height	410 mm	Depth	100 mm	Built-in height	80 mm
RAL-number	9003	Type of door	Single	Transparent cover/door	No
With lock	No	Inner depth	80 mm	Number of rows	2
Extension possible	No	Housing material	Plastic	With mounting plate	No
Type of closure	Push button	Earthing terminal block	Yes	Neutral terminal block	Yes
DIN-rail	Yes	EMC-version	No		

Technical Characteristics

dimensions

430x410x80 mm

Power dissipation

52 W

Dimensions and technical drawings

EC63336_COPERCHIO_2025.pdf



EC63536_FONDO_2025.pdf

Barcode



8056351666824

Unit

1 NR

0.42x0.45x0.16 [m]

2.717 [kg]