



EC69003

BLANK BOARDS FOR 4 SOCKETS - 8 MOD.



Industrial > Distribution boards > Distribution boards > Unwired versions > Small distribution board > 4 sockets - 8 modules

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Description

Distribution board for modular devices and industrial sockets. Made of shock-resistant ABS-based technopolymer. Galvanized steel DIN rail mounted on the bottom and depth-adjustable. Knockouts for pipe or cable entry with grommets, conduit fittings or cable glands of various sizes. Supplied as standard with screw caps for double insulation. Hinged cover. Door closure with triangular key included. Manufactured in compliance with EN 60670-1 and EN 60670-24 standards.

Blank model. Dimensions 200x430x95 mm. 8 DIN modules. Dissipable power 13 W

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board

Mounting method	Surface mounted	Degree of protection (IP)	IP65	Width in number of modular spacings	8
Colour	Grey	Width	200 mm	Height	430 mm
Depth	95 mm	Built-in width	194 mm	RAL-number	7035
UV resistant	Yes	Type of covering	Cover	Cover model	Closed
Type of door	Single	Transparent cover/door	Yes	With lock	Yes
Inner depth	68 mm	Number of rows	1	Extension possible	Yes
Housing material	Plastic	With mounting plate	No	Signal passing door	No
Type of closure	Three-square	Earthing terminal block	No	Neutral terminal block	No
DIN-rail	Yes	EMC-version	No		

Technical Characteristics

Power dissipation 13 W


Documentation available for download



Instruction booklet
Istruzioni
690_0423.pdf



Instruction booklet
Sinottico 690_1.pdf



Instruction booklet
Sinottico 690_2.pdf



Certification
Serie 690-
IMQ_CA02.03487_
2018.pdf

Dimensions and technical drawings



EC69003_2025.pdf

Barcode



8032793874355
Unit
1 NR
0.44x0.21x0.1 [m]
1.5 [kg]