

**EC6902200**

**ASSEMBLED DISTR. BOARD ASC TYPE 3  
VERT.SOCKETS IP44 2X2P+E-3P+E**

Industrial > Distribution boards > Distribution boards > Series asc - board system > Cee socket outlet combination (iec 60309) > 3x16 a vertical sockets



**Technical Symbols/Marks/Approvals**



**Norms**

EN 61439-1 EN 61439-4

**Etim**

**GROUP EG000014 - Industrial sockets/plug applications**

**CLASS EC000379 - CEE socket outlet combination (IEC 60309)**


<b>Power loss</b>	9 W	<b>Leakage current type</b>	AC	<b>Degree of protection (IP)</b>	IP44
<b>Colour</b>	Grey	<b>Width</b>	105 mm	<b>Height</b>	430 mm
<b>Depth</b>	95 mm	<b>Housing material</b>	Plastic	<b>Contact material</b>	CuZn
<b>Surface coating contacts</b>	Untreated	<b>Military model</b>	No	<b>Number of socket outlets with protective contact CEE 7/3 (type F)</b>	0
<b>Number of socket outlets Swiss standard type 13</b>	0	<b>Number of socket outlets Swiss standard type 15</b>	0	<b>Number of socket outlets Swiss standard type 23</b>	0
<b>Number of socket outlets Swiss standard type 25</b>	0	<b>Type of mains connection</b>	CEE 16 A	<b>Cable length</b>	4 m
<b>Protection</b>	Overcurrent switch	<b>Number of socket outlets Danish standard (earthing pin, type K)</b>	0	<b>CEE socket outlet 16 A</b>	3x16A xp xxxV
<b>CEE socket outlet 32 A</b>	None	<b>CEE socket outlet 63 A</b>	None	<b>CEE socket outlet 125 A</b>	None
<b>Other fixtures and/or empty locations</b>	0	<b>Earth leakage switch</b>	Earth leakage switch with IFN 30 mA (standard)	<b>Number of miniature circuit breakers (MCB)</b>	1
<b>Power supply/connection possibility</b>	Feeder cable with plug	<b>Number of poles mains connection</b>	5	<b>Diameter cable entry</b>	M25
<b>Handling</b>	Portable				

## Technical Characteristics


<b>Differential device</b>	1x4P 16A	<b>MV protection device</b>	combinato	<b>Maximum power that can be delivered</b>	10.5 kW
<b>Prese_16A_2P+T</b>	2	<b>Prese_32A_2P+T</b>	-	<b>Prese_16A_3P+N+T</b>	-
<b>Prese_16A_3P+T</b>	1	<b>Schuko/bivalent sockets</b>	-	<b>prese_32A_3P+T</b>	-
<b>Prese_32A_3P+N+T</b>	-				

## Documentation available for download

**Electical diagram**  
6902200-2210.pdf



## Barcode



8032793875116  
**Unit**  
1 NR  
0.505x0.275x0.155 [m]  
3.3 [kg]