



EC6902319

ASSEMBLED DISTR. BOARD BDO TYPE 4 GREEN SOCKETS IP55 P17/30



Industrial > Distribution boards > Distribution boards > Series asc - board system > Cee socket outlet combination (iec 60309) > E-bike charging wall box

Technical Symbols/Marks/Approvals



Norms

EN 61439-1 EN 61439-4

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC000379 - CEE socket outlet combination (IEC 60309)

Power loss	13 W	Leakage current type	AC	Degree of protection (IP)	IP55
Colour	Grey	Width	200 mm	Height	430 mm
Depth	95 mm	Housing material	Plastic	Contact material	CuZn
Surface coating contacts	Untreated	Military model	No	Number of socket outlets with protective contact CEE 7/3 (type F)	4
Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0	Number of socket outlets Swiss standard type 23	0
Number of socket outlets Swiss standard type 25	0	Type of mains connection	CEE 16 A	Protection	Overcurrent switch
Number of socket outlets Danish standard (earthing pin, type K)	0	CEE socket outlet 16 A	None	CEE socket outlet 32 A	None
CEE socket outlet 63 A	None	CEE socket outlet 125 A	None	Other fixtures and/or empty locations	0
Earth leakage switch	Earth leakage switch with IFN 30 mA (standard)	Number of miniature circuit breakers (MCB)	1	Power supply/connection possibility	1 cable (branch line)
Number of poles mains connection	5	Diameter cable entry	M25	Handling	Wall mounting

Technical Characteristics


Differential device	4x2P - 6A	MV protection device	combinato	Power Output Per Socket	1.3 kW
Maximum power that can be delivered	5.2 kW	Schuko/bivalent sockets	4 x P17/30		

Documentation available for download

Electical diagram
6902319.pdf



Barcode



8054382041436
Unit
1 NR
0.505x0.275x0.155 [m]
3.1 [kg]