

EC69058

**PANEL-MOUNT INCLINED SOCKET IP67 380/415V
3P+E 32A**



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Industrial > Plugs and sockets > Panel and wall-mount > Panel sockets > Panel-mounted cee socket outlet (iec 60309) > Ip67 - 32 a

Technical Symbols/Marks/Approvals



Norms

EN 60309-1 EN 60309-2

Description

EN 60309 industrial flush-mount socket. IP67 protection rating. 20° tilt. Pre-screwed screw terminals oriented in the same direction for quick wiring. Stainless steel cover springs. Panel gasket included. Recommended mounting with 3.5x16 or M4x20 self-tapping screws (not included).
3P+E 32A 380-415V~ 6h

Etim

GROUP EG000014 - Industrial sockets/plug applications
CLASS EC001317 - Panel-mounted CEE socket outlet (IEC 60309)

| | | | | | |
|-------------------------------------|-----------|----------------------------------|-----------|--|-------------------------|
| Number of poles | 4 | Degree of protection (IP) | IP67 | Material | Plastic |
| RAL-number | 3000 | IEC-amperage | 32 A | Voltage according to EN 60309-2 | 400 V (50+60 Hz) red |
| Clock hour position | 6 h | Identification colour | Red | Connection system | Screwed terminal |
| Insert direction | Straight | Surface coating contacts | Untreated | Military model | No |
| Rated voltage | 380-415 V | Rated frequency | 50-60 Hz | Flange size vertical | 97 mm |
| Drill hole distance vertical | 73 mm | Flange size horizontal | 80 mm | Drill hole distance horizontal | 60 mm |

Documentation available for download

Certification

IMQ_CA02.05864_2025_32A.pdf

Barcode



8032793876113

Unit

1 NR

0.3 [kg]



8059307215879

Pack

10 NR

0.19x0.285x0.23 [m]

3 [kg]



8033576778242

Cardboard

40 NR

0.405x0.605x0.355 [m]

12 [kg]