

**EC69059**

**PANEL-MOUNT INCLINED SOCKET IP67 380/415V  
3P+N+E 32A**



Industrial > Plugs and sockets > Panel and wall-mount > Panel sockets > Panel-mounted cee socket outlet (iec 60309) > Ip67 - 32 a

**Technical Symbols/Marks/Approvals**



**Norms**

EN 60309-1 EN 60309-2

**Description**

EN 60309 industrial flush-mount socket. IP67 protection rating. 20° tilt. Pre-screwed screw terminals oriented in the same direction for quick wiring. Stainless steel cover springs. Panel gasket included. Recommended mounting with 3.5x16 or M4x20 self-tapping screws (not included).  
3P+N+E 32A 346-415V~ 6h

**Etim**

**GROUP EG000014 - Industrial sockets/plug applications**  
**CLASS EC001317 - Panel-mounted CEE socket outlet (IEC 60309)**

<b>Number of poles</b>	5	<b>Degree of protection (IP)</b>	IP67	<b>Material</b>	Plastic
<b>RAL-number</b>	3000	<b>IEC-ampereage</b>	32 A	<b>Voltage according to EN 60309-2</b>	400 V (50+60 Hz) red
<b>Clock hour position</b>	6 h	<b>Identification colour</b>	Red	<b>Connection system</b>	Screwed terminal
<b>Insert direction</b>	Straight	<b>Surface coating contacts</b>	Untreated	<b>Military model</b>	No
<b>Rated voltage</b>	346-415 V	<b>Rated frequency</b>	50-60 Hz	<b>Flange size vertical</b>	97 mm
<b>Drill hole distance vertical</b>	73 mm	<b>Flange size horizontal</b>	80 mm	<b>Drill hole distance horizontal</b>	60 mm

**Documentation available for download**



## Barcode



8032793876120

**Unit**

1 NR

0.325 [kg]



8059307215909

**Pack**

10 NR

0.185x0.285x0.225 [m]

3.25 [kg]



8033576778211

**Cardboard**

40 NR

0.405x0.605x0.355 [m]

13 [kg]