

EC69088



MOBILE SOCKET IP44 380V 3P+N+E 32A

Industrial > Plugs and sockets > Portable > Sockets > Cee sockets (iec 60309) > Ip44 - 32 a



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 60309-1 EN 60309-2

Description

Industrial mobile socket type EN 60309. IP44 protection degree. Tool-free rapid assembly with 30° twist-lock system. Pre-loosened screw terminals oriented in the same direction for fast wiring. Cable locking nut with gasket. Stainless steel cover springs. 3P+N+E 32A 346-415V~ 6h

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001320 - CEE coupling (IEC 60309)

Number of poles	5	Degree of protection (IP)	IP44	Material	Plastic
RAL-number	7035	IEC-ampereage	32 A	Voltage according to EN 60309-2	400 V (50+60 Hz) red
Clock hour position	6 h	Identification colour	Red	Connection system	Screwed terminal
Cable entry	Gland nut	Insert direction	Straight	Contact material	CuZn
Surface coating contacts	Untreated	Military model	No		

Documentation available for download

Certification

IMQ_CA02.05870_2025_32A.pdf

Barcode



8032793876946

Unit

1 NR

0.325 [kg]



8059307216326

Pack

10 NR

0.19x0.285x0.225 [m]

3.25 [kg]



8033576777832

Cardboard

40 NR

0.4x0.6x0.35 [m]

13 [kg]