

EC690911



WALL-MOUNT HORIZ. INTERLOCKED SOCKET IP65 220V 2P+E 16A



Industrial > Plugs and sockets > Switched interlocked > Horizontal - without fuse holder > Cee socket outlet, disconnectable (iec 60309) > Ip65 - wall-mount

Technical Symbols/Marks/Approvals



Norms

EN 60309-1 EN 60309-2 EN 60309-4

Description

Interlocked switched surface-mounting socket. Protection rating IP65. Dimensions: 155x115x78 mm. 20° inclined socket. Switch type AC23A - 10 kA. Ergonomic handle padlockable in ON/OFF position. Stainless steel cover springs. 2P+E 16A 200-250V~ 6h

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)

Number of poles	3	Degree of protection (IP)	IP65	Model	Base unit and cover
Housing material	Plastic	IEC-amperage	16 A	Voltage according to EN 60309-2	230 V (50+60 Hz) blue
Clock hour position	6 h	Identification colour	Blue	Contact material	CuZn
Surface coating contacts	Untreated	Military model	No	Protection	None
Switch	Mechanical locking	With earth leakage switch	No	Empty locations on mounting rail	No

Documentation available for download

Certification

IMQ_CA02.05703_2025_16A IOSBF.pdf

Barcode



8032793877035

Unit

1 NR

0.125x0.19x0.135 [m]

0.6358 [kg]



8059307216517

Cardboard

24 NR

0.415x0.6x0.44 [m]

15.2592 [kg]