

EC690931F



**WALL-MOUNT HORIZ. INTERLOCKED
SOCKET WITH FUSE HOLDER IP65
380V 3P+E 16A**



Industrial > Plugs and sockets > Switched interlocked >
Horizontal - with fuse holder > Cee socket outlet,
disconnectable (iec 60309) > Ip65 - wall-mount

Technical Symbols/Marks/Approvals



Norms

EN 60309-1 EN 60309-2 EN 60309-4

Description

Interlocked switched surface-mounting socket with fuse base. Protection rating IP65. LED blown fuse indicator. gG type fuses 10.3x38 mm (not included). Dimensions: 196x146x77 mm. 20° inclined socket. Switch type AC23A - 10 kA. Ergonomic handle padlockable in ON/OFF position. Stainless steel cover springs. 3P+E 16A 380-415V~ 6h

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)


Number of poles	4	Degree of protection (IP)	IP65	Model	Base unit and cover
Housing material	Plastic	IEC-ampereage	16 A	Voltage according to EN 60309-2	400 V (50+60 Hz) red
Clock hour position	6 h	Identification colour	Red	Contact material	CuZn
Surface coating contacts	Untreated	Military model	No	Protection	Cylindrical fuse
Switch	Mechanical locking	With earth leakage switch	No	Empty locations on mounting rail	No

Documentation available for download



Certification
IMQ_CA02.05698_
2025_16A_IOCBBF.
pdf

Barcode



8033954871893
Unit
1 NR
0.2x0.154x0.145 [m]
0.858 [kg]



8059307216708
Cardboard
10 NR
0.605x0.4x0.35 [m]
8.58 [kg]